



FUNCTION

HSBLC ON



HSBLC OFF

FEATURES

SPECIFICATION

Smart IR ON

Smart IR OFF

- ► Ultra High Resolution (650TVL)
- ► Super Sensitivity (0.00002Lux)
- ► 2D+3D DNR (Digital Noise Reduction)
- ► Digital Slow Shutter (Sense-up)
- ► D-WDR (Wide Dynamic Range)
- ► Intelligent IR Control (Smart IR)
- ▶ 3.6mm Fixed Lens
- ► Weatherproof Vandal Resistant (IP66)
- ► Built-In High Power LED

ITEM		NTSC	PAL
С	TotalPixel	811(H) x 508(V)	795(H) x 596(V)
C	Effective Pixels	768(H) x 494(V)	752(H) x 582(V)
D	Sensor	1/3" SONY SUPER HAD II CCD	
	Scanning System	2:1 Interlace	
E L E C T R I C A L	Resolution	More than 650 TV Lines	
	Video Output	1.0Vp-p Composite Signal (750hm)	
	S/N (Y signal)	52dB (AGC OFF,Weight ON))	
	Min.Illumination	0.01Lux(Sense-up Auto 0.00002 Lux)	
	White Balance	AUTO/ATW/ MANUAL	
	Electronic shutter speed	1 / 60 sec ~ 1 / 100,000 sec 1 / 50 sec ~ 1 / 100,000 sec	
	3D-DNR (Digital Noise Reduction)	OFF / ON Selectable	
	Sense-Up	Auto/OFF(\sim x2 \sim x1024)	
	D&N Selection	AUTO / COLOR / BW / EXT	
	WIDE BLC (D-WDR)	OFF / ON Selectable	
	BLC	HLC/BLC/OFF	
	Defect Pixel Compensation	Built-In OSD	
	SMART LED Control	Built-In OSD	
	Motion Detection	ON/OFF	
	Privacy Masking	ON/OFF	
	Mirror	Built-In OSD	
	Sharpness	ON/OFF	
	Pan Focus Control	Built-In OSD	
	Multi Language	Available	
	O.S.D	Available	
	Operating temperature/Humidity	-10°C ~ 50°C/0-80% RH	
	Power Supply	DC 12V	
	Dimensions	64.2mm(H)x110mm(D)	

CEF©