



Features

- Support 16ch 4M unreal-time encoding;
- Support AHD, TVI,CVI, CVBS, IP video input;
- Support VGA maximum 1080P output, HDMI up to 4K output
- 1.5U Case, 2 SATA(Up to 8TB);
- 1*10/100Mbps auto-sensing Ethernet port, RJ45 port ;
- Automatic networking support, a key to add equipment;
- Support the Onvif protocol;
- Support GB28181 (Optional);
- Cloud services, P2P, alarm information push to phone;
- Support remote access, support ARSP;
- Support DHCP, FTP, DNS, DDNS, NTP, UPNP, EMAIL, Alarm center, etc ;
- Mobile phone remote monitoring (iOS, Android);
- Multi browser access (IE, Chrome, Firefox, Safari);
- Support for more than twenty languages;
- Perfect protection circuit,unique triple watchdog function
- Support WEB, CMS, VMS, MYEYE Platform;



	Model	PS-6616AQHD
System	processor	Hi3531A
Video	Codec	H.264+/H.264
	Encode	16*4M@8fps(AHD) ; 16*3M@10fps(AHD)16*1080P @15fps (5 in 1) ; 16*720P(5 in 1)
	Decode	8*4M@8fps(AHD) ; 8*3M@10fps(AHD) ; 8*1080P @15fps (5 in 1) ; 8*720P(5 in 1)
	Multi-mode	Analog:16*4M@8fps(AHD); 16*3M@10fps(AHD) ; 16*1080P @15fps (5 in 1) ; 16*720P(5 in 1)
		Hybird:8*4M(analog)+8*4M (network)
		IP: 8*3M ;4*5M
	Playback	8ch
	Compression	G.711a
	Audio	Intercom
Management	Record mode	Manual>Alarm>Motion detection>Timing
	Inquire mode	Inquire by Time/Calendar/Event/Channel
	Storage mode	HDD Storage, Network Storage
	Backup	Network, USB, SATA
Interface	Video input	16*BNC (Support Coaxitron)
	HDMI output	1*HDMI (MAX:4K)
	VGA output	1*VGA (MAX:1080P)
	Audio I/O	6/1
	Alarm I/O	4/1
	Ethernet port	1*10/100Mbps Ethernet port, RJ45 port
	PTZ control	1*RS485, Support for multiple PTZ protocol
	USB Port	2*USB2.0 ports
	HDD	2*SATA interface (Up to 8TB)
General	Temperature	0 °C - + 55 °C
	Humidity	10% -90% RH
	Power supply	12V/4A
	Consumption	<10W (Without HDD)
	Weight	Around 1.8KG
	Dimension	310mm(L)* 298mm(W)* 60mm(H)